

# Copper Tubing

## Features

- 1/4, 3/8, and 1/2 in. outside diameter seamless tubing
- ASTM B75
- 99.9 % pure
- O50 temper (light annealed)

## Material Standards

UNS	ASTM
C12200/DHP	B75

## Chemical Composition

Element	Composition wt. %
Copper	99.90 min
Phosphorous	0.015 to 0.040

## Ordering Information

Select an ordering number.

Nominal OD, in.	Nominal Wall Thickness, in.	Ordering Number	Nominal Length, ft	Product Form	Weight lb/ft	Allowable Working Pressure, psig
1/4	0.030	CU-T4-S-030-10	10	Straight	0.080	1380
		CU-T4-S-030-50	50	Coil		
3/8	0.035	CU-T6-S-035-10	10	Straight	0.145	1160
		CU-T6-S-035-50	50	Coil		
1/2	0.049	CU-T8-S-049-10	10	Straight	0.269	1220
		CU-T8-S-049-50	50	Coil		

## Pressure Ratings

See Swagelok® *Tubing Data*, MS-01-107, for complete pressure ratings.

## Tube Fittings

See the Swagelok *Gaugeable Tube Fittings and Adapter Fittings* catalog, MS-01-140, for more information.

### Safe Product Selection

**When selecting a product, the total system design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user.**

## Tools and Accessories

See the Swagelok *Tools and Accessories* catalog, MS-01-169, for more information.



## Warranty Information

Swagelok products are backed by The Swagelok Limited Lifetime Warranty. For a copy, visit [swagelok.com](http://swagelok.com) or contact your authorized Swagelok representative.